

Lovász Local Lemma, Part 2

Recall the general version of LLL:

Thm: Let $B_1, \dots, B_n$ be a set of "bad" events, and let d be a bound on the max degree in the dependency graph. Then if:

$$\forall i, \Pr[B_i] \leq x_i \prod_{\substack{(i,j) \text{ edge} \\ \text{in dep graph}}} (1 - x_j) \text{ for } x_i \in [0, 1)$$

$$\text{then } \Pr\left[\bigwedge_{i=1}^n \overline{B_i}\right] \geq \prod_{i=1}^n (1 - x_i) > 0.$$

Remarks:

(1) Even if $d=0$, $\Pr[\bigwedge \overline{B_i}]$ is exponentially small.
So, LLL as above is non-constructive.

(2) Often times, each B_i is a function of subset S_i of an underlying set of independent random variables $X = \{x_1, \dots, x_N\}$. Then, we want $\forall i, \#\{j: S_i \cap S_j \neq \emptyset\} \leq d$.

Example: k -SAT with N variables and with each var occurring in $\leq \frac{d}{k}$ clauses.

Corollaries:

Symmetric LLL: If $\forall i, \Pr[B_i] \leq p$ and $ep(d+1) \leq 1$,

then $\Pr[\bigwedge \overline{B_i}] > 0$.

Pf: Set $x_i = \frac{1}{d+1}$

Asymmetric LLL: If $\forall i, \sum_{\substack{(i,j) \\ \text{dependent}}} \Pr[B_j] \leq \frac{1}{4}$, then $\Pr[\bigwedge \overline{B_i}] > 0$.


Pf: Set $x_i = 2 \cdot \Pr[B_i]$.

Packet Routing in Networks [Leighton-Maggs-Rao]

Network with bidirectional channels; n packets where i 'th packet τ_i from s_i to t_i thru path P_i .
... as thru

Each node has a queue and only one packet can go on an edge in one step. If more than one packet arrives at a node at the same time, one packet goes thru and others are queued. Synchronized.

Ex:



Goal: Prepare a schedule that minimizes time for all packets to reach destination.

Two key parameters: (1) d = Dilation
= Length of longest path P_i
(2) c = Congestion
= $\max_e [\# \text{ paths passing thru } e]$

Observation 1: $\text{OPT}_{\text{Time}} \geq \max(c, d) = \Omega(c + d)$

Observation 2: $\text{OPT}_{\text{Time}} \leq c \cdot d$

Lemma: $\text{OPT}_{\text{Time}} = O(c + d \log(nd))$

Pf sketch: Delay packet i by T_i , uniformly chosen from $[1, \frac{\alpha c}{\log(nd)}]$, then send to destination, for a large constant α .
Then, max # of packets going thru any edge is $O(\log(nd))$ whp.
Why? For any fixed edge e and time t ,

$$\Pr[> \log(nd) \text{ packets passing thru } e \text{ at } t] \leq \sum_{k=\log(nd)+1}^c \binom{c}{k} \left(\frac{\log(nd)}{\alpha c}\right)^k \left(1 - \frac{\log(nd)}{\alpha c}\right)^{c-k}$$

$$\leq \sum_{k=\log(nd)+1}^c \left(\frac{e \log(nd)}{\alpha k}\right)^k \leq c \cdot \left(\frac{e}{\alpha}\right)^{\log(nd)} \leq \frac{1}{(nd)^5}$$

$$\Pr[\exists e, t, > \log(nd) \text{ passing thru } e \text{ at } t] \leq \frac{1}{nd}$$

therefore packets one at a time to make schedule feasible.

$$\text{Total time} \leq \log(nd) \cdot \left(d + \frac{\alpha c}{\log(nd)}\right) = O(c + d \log(nd))$$

$$\text{Max Queue Size} \leq \log(nd)$$

What happens if we use LLL instead of union bound?

Suppose delays are random in $\left[\frac{\alpha c}{\log(cd)}\right]$

B_e is event that $\geq \log(cd)$ packets pass thru e at some time.

Degree of dependency graph is $\leq c \cdot d$.

$$\Pr[B_e] \leq \left(d + \frac{\alpha c}{\log(cd)}\right) \cdot \sum_{k=\log(cd)}^c \binom{c}{k} \cdot \left(\frac{\log(cd)}{\alpha c}\right)^k \leq \frac{1}{e c^2 d^2}$$

Then, $e \cdot \Pr[B_e] \cdot (cd+1) \leq \frac{1}{cd} < 1$. By LLL, result follows.

Then, total schedule time $\leq O(c + d \log(cd))$

Queue length $\leq O(\log(cd))$

By using divide and conquer, and careful parameter tuning, we can bring down schedule time to $O(c+d)$ and queue length to $O(1)$!

Constructive LLL

- Event guaranteed by LLL has exponentially small probability. But we want to efficiently find a point in sample space where event occurs!
 - Get back to k -SAT example. If each clause intersects with $\leq 2^k/e$ clauses, then LLL guarantees satisfying assignment. How to find it efficiently?
 - Note that even when clauses are disjoint, random assignment is satisfying with exponentially small prob. But then finding a sat assignment trivially in poly time!
- ... result by Ph.D. student Robin Moser in '09 ... $k-3$ later

finds sat. assignment if clause overlap is ≤ 2 , improved to the optimal $2^{k/e}$ by Moser and Tardos.

Algorithm:

Solve (φ):

Pick a random assignment A for $x_1, x_2, \dots, x_n$

While A violates a clause C :

$A \leftarrow \text{Fix}(C, A)$

(*)

return A

Fix (C, A):

For variable v in C :

Set $A(v)$ randomly

While $\exists$ clause D overlapping with C that A violates:

$A \leftarrow \text{Fix}(D, A)$

(**)

↑ In fact, this last if can be omitted!!

(***)


return A

Claim: If Fix terminates, then assignment returned by $\text{Fix}(C, A)$ satisfies C and doesn't violate any clause which A satisfied.

Pf: Easy.

So, number of violated clauses keeps decreasing if Fix terminates. But how do we show that?

Imagine all random bits needed laid out before the algorithm.



If Fix is called $> m \lg m$ times, then contradiction!

The first $n + k n \lg m$ bits of X can be compressed...
(Entropy compression)

Compression procedure:

- If Fix is called in line (*), change first n bits to new assignment and replace block by $\lg m$ -size clause id.
- If Fix is called in line (**), change first n bits to new assignment and replace block by i if D is the i 'th clause intersecting C .
- At line (***) , insert a special "RET" symbol after the last edited block.

After T calls of Fix , length of string is

$$\leq m \lg m + T(\lg d + O(1)) + n$$

Note that compression is reversible, because unique ass violates a clause.

$$n + Tk \geq m \lg m + T(\lg d + O(1)) + n$$

$$= T(\lg d + O(1))$$

$$\text{if } T = m \lg m$$

$$\lg d \leq k - O(1)$$

$$d \leq 2^{k - O(1)}$$

Done!