

# Future Directions for Mobile-Agent Research

David Kotz, Robert Gray, and Daniela Rus

*Based on a conversation with*

Jeff Bradshaw, Colin Harrison, Günter Karjoth, Amy Murphy,  
Gian Pietro Picco, M. Ranganathan, Niranjani Suri, and Christian Tschudin

**Technical Report TR2002-415**

**Department of Computer Science, Dartmouth College**

January 29, 2002

## Abstract

During a discussion in September 2000 the authors examined the future of research on mobile agents and mobile code. (A *mobile agent* is a running program that can move from host to host in network at times and to places of its own choosing.) In this paper we summarize and reflect on that discussion. It became clear that the field should shift its emphasis toward mobile code, in all its forms, rather than to continue its narrow focus on mobile agents. Furthermore, we encourage the development of modular components, so that application designers may take advantage of code mobility without needing to rewrite their application to fit in a monolithic mobile-agent system. There are many potential applications that may productively use mobile code, but there is no “killer application” for mobile agents. Finally, we note that although security is an important and challenging problem, there are many applications and environments with security requirements well within the capability of existing mobile-code and mobile-agent frameworks.

## 1 Introduction

Last year several mobile-agent researchers gathered for a dinner and discussion of the future directions in mobile-agent research. The September 2000 event was the most recent in our series of Dartmouth Workshops in Transportable Agents, and was held in Zurich immediately following ASA/MA 2000 (the joint conference on Agent Systems and Applications and on Mobile Agents). Biographies of the participants appear in the appendix.

---

The authors can be reached at the Department of Computer Science, Dartmouth College, Hanover, NH 03755-3510, {First.Last}@dartmouth.edu. This event was supported by DoD MURI contract F49620-97-1-03821.

Our purpose was to identify key research directions that will allow mobile-agent research to have an impact beyond the immediate mobile-agent research community, to other research areas in computer science and to the commercial world. This article summarizes and reflects on the most important themes in that discussion.

The text of this article represents an amalgamation of the comments made during the discussion, not necessarily the opinions of the authors and not necessarily a unanimous consensus of those attending. In summarizing, we attempt to present the main ideas and the general sense of the discussion.

## 2 Background

A *mobile agent* is a running program that can move from host to host in network when and where it chooses. Mobile agents are one form of mobile code. In its simplest form, the concept of mobile code involves the dynamic installation of code on a remote host. In Web applications, applets and servlets are a common form of mobile code. The mobile code concept also appears in “remote evaluation” systems [SG90], which extend the notion of remote procedure call to transport the procedure to the server along with the call. Many researchers extend the mobile-code concept to “mobile objects,” in which an object (code and data) are moved from one host to another. The mobile-agent abstraction extends this notion further, by moving code, data, and a thread from one host to another. A mobile agent runs in one location, moves (with its state) to another host, and continues at that host. Mobile code and mobile objects are normally moved by an external entity; mobile agents usually have migration autonomy.

Mobile agents have many potential advantages. By moving the computation to another host it is often pos-

sible to co-locate the computation with an important database, allowing high-throughput low-latency access to that database. Compared to more traditional client-server approaches, mobile agents can avoid transmitting as much data across the network, which is of particular value when the network is slow or unreliable (as in the Internet, or wireless networks). The mobile agent can move, with partial results, from one server to another until it has accomplished its task, and then return to the originating host, which may freely be disconnected during the agent's travels.

In addition to speed and reliability improvements, mobile agents can also be helpful in structuring many distributed applications. A service that wishes to relocate itself in the network to accommodate changing network conditions or the changing location of its clients can easily be written as a mobile agent [RASS97, APGG00, BPR98]. A client that wishes to trace the path of an intruder through a network of hosts can be written as a mobile agent that scans host logs, identifying the source of the intrusion and jumping to that host for further tracking.

*“We’re trying to separate the logical design of the system from the placement of its components.”*  
— M. Ranganathan

There are many existing mobile-agent systems,<sup>1</sup> but few (if any) will fully meet the needs of programmers of large, complex applications. There are few commercial mobile-agent systems, and fewer standards, available. Clearly one of the tasks ahead, if mobile agents are to have significant impact, is to identify the key features that make mobile agents successful, extract those features into a coherent, flexible set of composable software tools, and arrive at a standard interface.

### 3 Monolithic systems

Throughout the discussion there was a general sense that the mobile-agent community should be shifting its emphasis away from mobile-agent systems.

For the last seven or eight years, our nascent research field has seen the development of initial technology for mobile agents. Researchers and developers put together the basic technology and tested how well the (many) needed subsystems interacted with each other.

This initial research phase was quite successful. Consider the work published in the “Mobile Agent” series of conferences (MA97, MA98, ASA/MA99, and MA2000), an incomplete but significant portion of

<sup>1</sup><http://www.informatik.uni-stuttgart.de/ipvr/vs/projekte/mole/mal/mal.html>

the relevant research. There was a lot of promising work on specific features in mobile-agent systems, including persistence [dSdS97], resource allocation [Tsc97, LP99], orphan detection [BR98], state capture [Fün98, WBDF98, SBB+00a, SSY00, TRV+00], security [BMW98, KAG98, Fün99, BV99, Kar00], communication [CLZ00, MP99, RSGM99, RBM00], coordination [CLZ00], and languages [WS99, DELM00]. These conference proceedings also present several robust and efficient, albeit monolithic, mobile-agent systems, such as AgentSpace [SdD98], Ara [PS97], Concordia [WPW+97], and NOMADS [SBB+00b]. One,  $\mu$ Code [Pic98], is a modular toolkit that supports a variety of mobility paradigms.

During our discussion Gian Pietro Picco noted that this monolithic approach to mobile-agent systems is hurting the spread and acceptance of mobile code. Developers are hesitant to develop applications that require them to use a new, large, monolithic system. In addition, since the monolithic systems are usually not tailored to specific application domains, and thus include significant overheads that are not needed for many applications, the performance benefits of mobile code in general have not yet been made completely clear. Indeed, there few quantitative performance results yet published about mobile agents. So far, there has been little motivation for developers to use mobile agents.

Thus the mobile-agent community must make a concerted effort to move away from the monolithic systems—in fact, to move away from the idea of large, completely autonomous mobile agents—and instead apply the *idea* of mobile code to specific applications, using whatever form of mobile code the application suggests or demands. Many of the subsystems developed as part of the mobile-agent systems will find their way into these applications, but it is no longer productive to try to take a monolithic system that has all the subsystems and try to make that system fit the application (or more precisely, bend the application to fit the system). In our discussion we considered component-based architectures at length (see the next section). Existing research suggests the provision of mobility components in a toolkit [Pic98]. Others propose to construct mobile agents out of existing mobile [GFP99] or non-mobile [QV99] components.

Furthermore, to justify the claims that we make as mobile-agent researchers, research should whenever possible include a detailed quantitative evaluation of the value of mobility. In the recent Mobile Agent conference series, there are few such papers [Tsc97, Fün98, WBDF98, Joh98, KP98, SH99, SDSL99, LP99, TR99]. Other notable papers include [BPR98, FPV98, BGM+99]. Quantitative justification for improved performance is necessary to convince others about when and how mobility can help them.

## 4 Architecture and Components

During the discussion it became clear that it is important to distinguish between the use of mobile-agent concepts as an architecture for your application, and the use of a specific mobile-agent system to implement your application.

*“Code mobility is a new way to look at how you structure an application. You’re thinking in a different way from mainstream distributed computing, and that’s the power. The power is not in the technology, it’s in the architecture.”*  
— Gian Pietro Picco

Despite the value of mobile agents as a programming abstraction, it is often unexpectedly difficult for a programmer to consider adding mobility to an existing application. To use a mobile-agent system, programmers must typically make significant changes to their application so that it conforms with the language and constraints of the mobile-agent system.

*“Most mobile agent systems try to solve ten problems at the same time. They tend to be monolithic. People who want to only use one little slice of the system have to install the whole thing.”*  
— Gian Pietro Picco

Furthermore, most mobile-agent systems provide only one form of mobility, although there are actually several possible forms (such as applets, servlets (remote evaluation), mobile agents with weak mobility, and mobile agents with strong mobility). Each form of mobility is useful in different situations [FPV98].

*“You have client-server... you have mobile agents. There’s a lot of stuff in between that has not been addressed.”*  
— Gian Pietro Picco

Gian Pietro Picco pointed out that the software industry has evolved a component architecture for many large software systems, and proposed that mobile-agent systems be structured as a set of mobility components. At least, mobile-code and mobile-agent systems should interoperate with existing mechanisms, such as RMI communication, wherever possible. Furthermore, the current variety of features in mobile-agent systems would be available

as a set of orthogonal components, so that programmers could “plug in” components as needed for their application. One component might provide mobility, another security, another a certain form of communication.

*“You should have some way to add mobility only when it’s needed in your application.”*  
— Gian Pietro Picco

This component-based approach would allow much more flexibility for the programmer than we have seen in most mobile-agent systems so far. The challenge, then, is to distill the ideas that have evolved in the mobile-agent community into a set of standard, reusable, orthogonal components that can be combined as needed.

Not everyone was convinced that the component approach would work. Some thought that it may be too much work to build up an application out of small components, that many programmers want a monolithic integrated system as a starting point. Others thought that it may be quite difficult to actually produce orthogonal, reusable components.

*“One research direction is to look for a continuum of different abstractions from simple mobile code to mobile agents. From a simple base you could keep adding abstractions as you need them.”*  
— David Kotz

Christian Tschudin noted that there are many layers in which mobile agents and mobile code may be useful. It is most frequently discussed in the application layer, but in many cases it may be more valuable inside a middleware layer, supporting more conventional applications. In the Active Networking field, of course, mobile code is used in the network and routing layers. Even lower, there was some mention of using mobile code to program software radios, e.g., to install a new radio protocol that is needed to communicate with towers in the geographic vicinity.

Recently the mobile-agent community has focused on Java as a base language for implementing its ideas. Although convenient, Java does not have all of the necessary features. Ideally, a mobile-agent system should support multiple languages to accommodate the different needs of a variety of applications. Challenges for the community, then, are to determine which features need to be pushed into languages, and to find ways to make the components mentioned above work across multiple languages.

Indeed, as M. Ranganathan suggested, in many application domains it may be better not to use a general-purpose programming language. Give the user a set of compo-

*“To make mobility routine we need to address the language foundation. In addition to mobility, Java is missing fine-grain resource control and security.”*  
— Jeff Bradshaw

nents, tested and certified by the network administrator, and a simple language for composing components into mobile agents. For simple composition languages it may be possible for the system to derive guarantees on the size, resource consumption, and activity of the mobile agent that would not be possible in a more general-purpose programming language.

## 5 Education and Applications

*“People don’t use mobile code because they don’t realize that it’s useful. A lot of things come down to education, to awareness.”*  
— Amy Murphy

To have an impact on the world outside of the mobile-agent research community we, as researchers, must educate those in other fields of research and those in application development that mobile agents are a valuable tool. We discussed several steps that would help achieve that goal: 1) encourage more quantitative studies on the value of mobility and of the component-based approach to mobile-application development, 2) develop real applications that demonstrate the value of mobility and components, 3) develop standard interfaces and protocols to encourage compatibility and re-use, 4) develop solid practical solutions to the security and resource-control challenges of mobile agents, and 5) encourage faculty to teach about mobile code in courses on distributed systems.

### 5.1 Applications

Perhaps one of the most significant ways to demonstrate the value of mobile code is to develop prototype applications in which the value becomes apparent. In the Mobile Agent conferences there are several good examples, including the use of mobile agents in negotiating and monitoring quality of service for multimedia applications [OOC97], network management [BGP97, PPC99], videoconferencing [BPR98], or information dissemination [TR99]. Some papers evaluated multiple applications or implemented the same application in multiple ways [GV97, Joh98, BJP+00].

During our discussion we identified a range of other applications, including Web servers (migrating to optimize their network position), network-edge servers (dynamically installed to cache content), active documents, spacecraft (due to the high inter-planetary latency, mobile code may offer better performance), network management (dynamically deployed monitoring tools), and network games.

*“We believe that web hosting is a common application for mobile code. Imagine a web server that moves itself from around in the network to optimize its position relative to the people currently using it.”*  
— Colin Harrison

Amy Murphy pointed out that it is important to remember that many of these applications may be implemented in “closed” networks, such as “intranets,” where a single developer controls all of the hosts and all of the agents. A university may allow mobile agents to circulate to allow large scientific calculations to run during idle moments on university-owned workstations. A telecommunications company may choose to use mobile code in its network-management application.

*“In IP telephony I see a real application for mobility, for example, a call-processing program that handles calls while you are disconnected.”*  
— M. Ranganathan

As mentioned earlier in a comment from Christian Tschudin, “we should aim for something that is very invisible,” notably the middleware. It may often be more appropriate to use mobile-code inside the middleware for an application domain, rather than in the applications themselves. The application itself may not move, or be aware of the use of mobility, but some of the abstract services provided by its middleware may take advantage of mobility. An application using a database, for example, may be unaware that its queries are encoded into numerous bits of mobile code sent to remote data warehouses.

It was clear that there is no “killer app” for mobile agents. Indeed, the participants were skeptical that any would be found; if, as Gian Pietro Picco believes, mobile agents are a design technique, not an enabling technology, the designer of any distributed application should consider the use of mobile code in some form. Still, Günter Karjoth encouraged everyone to look for applications with “sequential matchmaking,” in which the application must perform a sequence of activities involving data or ser-

vices on multiple hosts. Of course, the same application could be implemented with a sequence of remote procedure calls, but under the right circumstances this sort of application may demonstrate the value of multi-hop mobile agents.<sup>2</sup>

*“People want to support mobile devices with scalable services located at the edge of the network. The ability to migrate functionality right into these services is going to be very important.”*  
— Colin Harrison

Jeff Bradshaw and Colin Harrison suggested that in the future software may not be distributed to end-user computer systems. Instead, the software author would send it to an Application Service Provider (ASP) host, where the software registers itself as a service. End users then use that service over the Internet. Any components that need to be on the end-user machine would be installed when first needed. It is possible that mobile code could be helpful in both installation procedures. Others at the table were concerned about the potential security problems as well as the potential for unforeseen interactions between services or components.

An alternative suggested by Niranjani Suri was Service Composition. Although an ASP may not be comfortable allowing you to upload complex code to their site, they may be willing to let you run simple code, e.g., code with no loops, that makes calls to existing services on the ASP.

Although we did not discuss any applications in detail, there was clear interest in seeing more researchers implement these sort of applications, in multiple ways (without mobile code, and with a variety of forms of mobile code), analyze the different solutions quantitatively and qualitatively, and publish papers on the advantages and disadvantages of mobility in those applications.

## 6 Security

In our discussion of security, two things became very clear: 1) security is hard, and 2) security is not always important. Indeed, many if not most applications for mobile code and mobile agents do not need these problems to be solved. For example, many applications occur inside “closed” systems. The security challenges here are much more limited than in the general “open-system” case. As a community we should encourage the development of applications or middleware based on the concept of mobile

<sup>2</sup>Single-hop mobile agents move from a client to a server, and perhaps back to the client. Multi-hop mobile agents visit more than one server before returning to the client.

code, wherever their security requirements fit within our current limitations.

That said, the remaining security problems fit into two categories: protecting host systems and networks from malicious agents, and protecting agents from malicious hosts.

There are many mechanisms to protect a host against malicious agents. Digital signatures and trust-management approaches may help to identify the agent and how much it should be trusted. But what then is the policy, what access and how much access do certain agents receive? This area needs a lot more work.

*“I think that we have quite well identified the threats against mobile-agent systems. Unfortunately for the most interesting ones we don’t have answers.”*  
— Günter Karjoth

The “malicious host problem,” in which a malicious host attacks a visiting mobile agent, is the most difficult and largely unsolved. Consider that, to execute the agent and update its state, the host must of course be able to read and write the agent. A malicious host might steal private information from the agent, or modify the agent to compute the wrong result or to misbehave when it jumps to another site. Günter Karjoth and Christian Tschudin have both addressed this problem, for example, by encrypting the agent’s code in such a way that it can compute on encrypted input and produce encrypted output, which when decrypted is the output that would have been produced by running the original input through the original code [Tsc99]. Unfortunately this approach currently works only for certain classes of polynomials, not general code.

## 7 What should we not do?

There is an unfortunate tendency to reinvent ideas from earlier research in distributed computing, relabel the ideas in the mobile-computing or mobile-agent context, and republish. We should of course embrace ideas from other fields, identify which ideas are useful and which are not in the context of mobility, but avoid reinventing these ideas.

It is definitely *not* a good idea to over-sell the value of mobility. Mobility is useful in some but not all situations. The goal of our research should be to help the broader community understand when, and how much, mobility might be of use.

## 8 Summary

The primary theme of our discussion could perhaps be summarized in one sentence: “The future of mobile agents is not specifically *as mobile agents*.” The concepts developed in the mobile-agent community have value in many situations, but the monolithic mobile-agent systems developed in the past decade are not necessarily the vehicle for those concepts to have an impact. The sub-themes in the discussion centered on components, education and awareness, applications, standards, and security.

Recent years have seen the development of many mobile agent systems, based on several slightly different semantics for mobility, security, communication, and the like. The community now needs to begin to distill the best of these ideas from all of the proposed approaches, and identify the situations where those approaches best apply. We need quantitative measurements of the value of each form of mobility, communication, and so forth. We need qualitative analysis of the value of these ideas in helping to structure distributed applications. Specifically when, where, and why are different forms of mobility useful? We need to remember that Java is not the only language, that multi-language support is important, and that it is important to isolate the value of our ideas from their implementation in a particular language platform.

Once we have identified and quantified the key concepts and ideas, we need to develop an infrastructure that would encourage the development of orthogonal, reusable components that implement those ideas. The infrastructure would begin with a minimal base and allow the programmer to add only those components, those *abstractions*, that are needed for that application.

As a community we need to reach out to other research and development communities, both to spread awareness of the value of mobile code (without over-selling!) and to become more aware ourselves of the types of applications that may benefit from our ideas. We can monitor other research communities, such as distributed computing, programming language, security, and software-engineering communities, adapting their ideas to the world of mobile computers and mobile code.

Eventually, many of the distilled ideas can be formed into a set of standards that can encourage the incorporation of the ideas into more applications. It still seems too early to begin that process.

We need implementations of real applications that demonstrate the value, with meaningful analyses of the benefits of mobile code in those applications. There were two specific ideas that might encourage real application development. One was to create a contest to award a prize to the best network game based on mobile code. Another was to encourage all mobile-agent research groups to enhance their web site with a mobile-agent platform, so that

mobile agents could visit their web site. The resulting set of sites could be an interesting proving ground for mobile-agent applications.

In the end, the mobile-agent research community should strive to contribute by improving our understanding of the value of mobility, by distilling our ideas into a core set of concepts, by encouraging the construction of those concepts as a set of composable software components, by educating those outside our community about the value of mobility, and by demonstrating its value through the its use in real applications and middleware.

## Biographies

**Jeff Bradshaw** is a research scientist at the Institute for Human and Machine Cognition at the University of West Florida. Previously, Dr. Bradshaw led the intelligent agent technology group at The Boeing Company, where he was responsible for the development of the KAoS agent framework and its use in applications such as the NASA-sponsored Aviation Extranet and the DARPA control of agent-based systems (CoABS) program. He is a member of the NASA team developing agent-based software for the Personal Satellite Assistant (PSA), a softball-sized flying robot for use by astronauts in the shuttle and the International Space Station. Jeff is chair of the RIACS Science Council for NASA Ames Research Center and chair of ACM SIGART.

**Bob Gray** is a Research Engineer in the Thayer School of Engineering at Dartmouth College, an Adjunct Professor in the Department of Computer Science, and a Research Engineer in the Institute for Security Technology Studies. His current research, which is funded by the Department of Defense, DARPA, and the National Institute of Justice, focuses on the performance and scalability of mobile agents and other forms of mobile code, and on information-retrieval tools for law enforcement personnel. Bob received a B.S. in Computer Science from the University of Vermont in 1993 and a Ph.D in Computer Science from Dartmouth College in 1997.

**Colin Harrison** is Director of Global Services Research at the IBM T. J. Watson Research Center in New York. Following his thesis work in materials science at Imperial College, London, he spent several years at CERN developing the real-time control system for the SPS accelerator. He then returned to EMI Central Research Laboratories in London, and lead the development of the world's first clinically-useful MRI system. He joined IBM in San Jose and has enjoyed a career leading from magnetics, to medical imaging, parallel computing, mobile networking, intelligent agents, telecommunications services, and knowledge management. He now has broad responsibility for the application of research skills in IBM's services businesses and is leading the establishment of new program in e-Learning.

**Günter Karjoth** is a research staff member in the computer science department at the IBM Zurich Research Laboratory. He has done research in the fields of protocol engineering and network security, with a current focus on access control in distributed object systems. His research interest is in the modeling of distributed systems, their validation and implementation.

**David Kotz** is an Associate Professor of Computer Science at Dartmouth College, Hanover NH. He received the M.S. and Ph.D degrees in computer science from Duke University in 1989 and 1991, respectively. He received

the A.B. degree in computer science and physics from Dartmouth College, Hanover NH, in 1986. He rejoined Dartmouth College in 1991 and was promoted with tenure to Associate Professor in 1997. His research interests include mobile agents, parallel and distributed operating systems, multiprocessor file systems, and computer ethics.

**Amy Murphy** received a B.S. in Computer Science from the University of Tulsa in 1995, M.S. and D.Sc. degrees from Washington University in St. Louis, Missouri in 1997 and 2000 and is currently an Assistant Professor in the department of Computer Science at the University of Rochester in Rochester, New York. Her research interests include the development of standard algorithms for mobility and the design, specification, and implementation of mobile middleware systems. These topics are integrated under the theme of enabling the rapid development of dependable applications for both physically and logically mobile environments.

**Gian Pietro Picco** is an Assistant Professor at the Department of Electronics and Information at Politecnico di Milano, Italy. Prior to this current appointment, he was a Visiting Assistant Professor at Washington University in St. Louis, Missouri, USA. His research interests are in distributed systems that exhibit mobility, be it logical or physical. His work in this area thus far has investigated several aspects spanning from theoretical models to systems research, and has led to several publications, some of which are widely referenced by the research community.

**M. Ranganathan** is a Computer Engineer in the Advanced Networking Technologies division of the National Institute of Standards and Technology (NIST). He holds M.S. Degrees in Mechanical and Electrical Engineering from the University of Illinois at Chicago, and an M.S. in Computer Science from the University of Maryland. He holds a B Tech. degree in Mechanical Engineering from the Indian Institute of Technology, Madras. His professional life includes 4 years as a Mechanical Engineer designing heat-transfer and plastics processing equipment and 16 years as a Computer Engineer. As a Computer Engineer, in the IBM Corporation Ranganathan contributed to the design and development of the memory-manager component of the OS/2 kernel and worked on workstation- and network-security issues for AIX and OS/2. At the University of Maryland, Ranganathan developed a mobile-agent platform called Sumatra that incorporated thread mobility into the Java Virtual Machine. At NIST, under DARPA funding, Ranganathan developed a re-configurable distributed event-oriented scripting platform called AGNI, applied it to building collaborative environments and distributed test systems, and studied issues relating to peer-to-peer communication in such environments. His current technical interests are in signaling, service creation, routing and quality of service for IP tele-



phony.

**Daniela Rus** is an associate professor in the Computer Science Department at Dartmouth College, where she founded and directs the Dartmouth Robotics Laboratory. She also co-founded and co-directs the Transportable Agents Laboratory and the Dartmouth Center for Mobile Computing. She holds a Ph.D degree in computer science from Cornell University. Her research interests include distributed manipulation, 3d navigation, self-reconfiguring robotics, mobile agents, and information organization. She is an Alfred P. Sloan Foundation Fellow and holds an NSF Career award.

**Niranjan Suri** is a Research Scientist at the Institute for Human and Machine Cognition (IHMC) at the University of West Florida. His recent research led to the development of the NOMADS mobile agent system for Java-based agents with secure execution and anytime and forced mobility. He developed and implemented a Java-compatible Virtual Machine with key extensions to support mobile state and resource control within the Java environment. His research interests include virtual machines, distributed computing, autonomous intelligent agents, network security, distributed, persistent objects, and Internet-based collaboration tools.

**Christian Tschudin** is an Associate Professor at Uppsala University, Sweden. He graduated in Mathematics, Physics and Sociology at the University of Basel, Switzerland in 1986 and received his PhD in computer science at the University of Geneva in 1993 on a computer network architecture based on mobile code. Before taking the position in Sweden, he was at the International Computer Science Institute, Berkeley, USA, and also worked

at the University of Zurich as a senior research associate. His research interests revolve around mobile code and include active (and wireless) networks, cryptography, market-based control, operating systems and artificial life.

## Acknowledgements

Many thanks to Jeff Bradshaw, Colin Harrison, Günter Karjoth, Amy Murphy, Gian Pietro Picco, M. Ranganathan, Niranjan Suri, and Christian Tschudin for their willingness to attend our conversation and to comment on drafts of this paper. Thanks to Wanda Bachmann for transcribing the tapes of the conversation, and thanks to the Hotel zum Storchen in Zurich for the excellent dinner.

## References

- [APGG00] Khalil Amiri, David Petrou, Gregory R. Ganger, and Garth A. Gibson. Dynamic function placement for data-intensive cluster computing. In *Proceedings of the 2000 USENIX Technical Conference*, pages 307–322. USENIX Association, 2000.
- [BGM<sup>+</sup>99] Brian Brewington, Robert Gray, Katsuhiko Moizumi, David Kotz, George Cybenko, and Daniela Rus. Mobile agents for distributed information retrieval. In Matthias Klusch, editor, *Intelligent Information Agents*, chapter 15, pages 355–395. Springer-Verlag, 1999.

- [BGP97] Mario Baldi, Silvano Gai, and Gian Pietro Picco. Exploiting code mobility in decentralized and flexible network management. In *Proceedings of the First International Workshop on Mobile Agents*, volume 1219 of *Lecture Notes in Computer Science*, pages 13–26, Berlin, Germany, April 1997. Springer-Verlag.
- [BJP<sup>+</sup>00] Ladislau Bölöni, Kyungkoo Jun, Krzysztof Palacz, Radu Sion, and Dan C. Marinescu. The Bond agent system and applications. In *Proceedings of the Second International Symposium on Agent Systems and Applications and Fourth International Symposium on Mobile Agents (ASA/MA2000)*, volume 1882 of *Lecture Notes in Computer Science*, pages 99–112, Zurich, Switzerland, September 2000. Springer-Verlag.
- [BMW98] Ingrid Biehl, Bernd Meyer, and Susanne Wetzel. Ensuring the integrity of agent-based computations by short proofs. In *Proceedings of the Second International Workshop on Mobile Agents*, volume 1477 of *Lecture Notes in Computer Science*, pages 183–194, Stuttgart, Germany, September 1998. Springer-Verlag.
- [BPR98] Mario Baldi, Gian Pietro Picco, and Fulvio Risso. Designing a videoconference system for active networks. In *Proceedings of the Second International Workshop on Mobile Agents*, volume 1477 of *Lecture Notes in Computer Science*, pages 273–284, Stuttgart, Germany, September 1998. Springer-Verlag.
- [BR98] Joachim Baumann and Kurt Rothermel. The shadow approach: An orphan detection protocol for mobile agents. In *Proceedings of the Second International Workshop on Mobile Agents*, volume 1477 of *Lecture Notes in Computer Science*, pages 2–13, Stuttgart, Germany, September 1998. Springer-Verlag.
- [BV99] Ciarán Bryce and Jan Vitek. The JavaSeal mobile agent kernel. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 103–116, Palm Springs, California, October 1999. IEEE Computer Society Press.
- [CLZ00] Giacomo Cabri, Letizia Leonardi, and Franco Zambonelli. MARS: A programmable coordination architecture for mobile agents. *IEEE Internet Computing*, 4(4):26–35, July 2000.
- [DELM00] Francisco Durán, Steven Eker, Patrick Lincoln, and José Meseguer. Principles of Mobile Maude. In *Proceedings of the Second International Symposium on Agent Systems and Applications and Fourth International Symposium on Mobile Agents (ASA/MA2000)*, volume 1882 of *Lecture Notes in Computer Science*, pages 73–85, Zurich, Switzerland, September 2000. Springer-Verlag.
- [dSds97] M. Mira da Silva and A. Rodrigues da Silva. Insisting on persistent mobile agent systems. In *Proceedings of the First International Workshop on Mobile Agents*, volume 1219 of *Lecture Notes in Computer Science*, pages 174–185, Berlin, Germany, April 1997. Springer-Verlag.
- [FPV98] Alfonso Fuggetta, Gian Pietro Picco, and Giovanni Vigna. Understanding code mobility. *IEEE Transactions on Software Engineering*, 24(5):342–361, May 1998.
- [Fün98] Stefan Fünfroeken. Transparent migration of Java-based mobile agents: Capturing and re-establishing the state of Java programs. In *Proceedings of the Second International Workshop on Mobile Agents*, volume 1477 of *Lecture Notes in Computer Science*, pages 26–37, Stuttgart, Germany, September 1998. Springer-Verlag.
- [Fün99] Stefan Fünfroeken. Protecting mobile Web-commerce agents with smartcards. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 90–102, Palm Springs, California, October 1999. IEEE Computer Society Press.
- [GFP99] Thomas Gschwind, Metin Feridun, and Stefan Pleisch. ADK - building mobile agents for network and systems management from reusable components. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 13–21, Palm Springs, California, October 1999. IEEE Computer Society Press.

- [GV97] Carlo Ghezzi and Giovanni Vigna. Mobile code paradigms and technologies: A case study. In *Proceedings of the First International Workshop on Mobile Agents*, volume 1219 of *Lecture Notes in Computer Science*, pages 38–49, Berlin, Germany, April 1997. Springer-Verlag.
- [Joh98] Dag Johansen. Mobile agent applicability. In *Proceedings of the Second International Workshop on Mobile Agents*, volume 1477 of *Lecture Notes in Computer Science*, pages 80–98, Stuttgart, Germany, September 1998. Springer-Verlag.
- [KAG98] G. Karjoth, N. Asokan, and C. Gülcü. Protecting the computation results of free-roaming agents. In *Proceedings of the Second International Workshop on Mobile Agents*, volume 1477 of *Lecture Notes in Computer Science*, pages 195–207, Stuttgart, Germany, September 1998. Springer-Verlag.
- [Kar00] Günter Karjoth. Secure mobile agent-based merchant brokering in distributed marketplaces. In *Proceedings of the Second International Symposium on Agent Systems and Applications and Fourth International Symposium on Mobile Agents (ASA/MA2000)*, volume 1882 of *Lecture Notes in Computer Science*, pages 44–56, Zurich, Switzerland, September 2000. Springer-Verlag.
- [KP98] Axel Küpper and Anthony S. Park. Stationary vs. mobile user agents in future mobile telecommunication networks. In *Proceedings of the Second International Workshop on Mobile Agents*, volume 1477 of *Lecture Notes in Computer Science*, pages 112–123, Stuttgart, Germany, September 1998. Springer-Verlag.
- [LP99] Manoj Lal and Raju Pandey. CPU resource control for mobile programs. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 74–88, Palm Springs, California, October 1999. IEEE Computer Society Press.
- [MP99] Amy L. Murphy and Gian Pietro Picco. Reliable communication for highly mobile agents. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 141–150, Palm Springs, California, October 1999. IEEE Computer Society Press.
- [OOC97] Luiz A. G. Oliveira, Paulo C. Oliveira, and Eleri Cardozo. An agent-based approach for quality of service negotiation and management in distributed multimedia systems. In *Proceedings of the First International Workshop on Mobile Agents*, volume 1219 of *Lecture Notes in Computer Science*, pages 1–12, Berlin, Germany, April 1997. Springer-Verlag.
- [Pic98] Gian Pietro Picco.  $\mu$ CODE: A Lightweight and Flexible Mobile Code Toolkit. In *Proceedings of the Second International Workshop on Mobile Agents*, volume 1477 of *Lecture Notes in Computer Science*, pages 160–171, Stuttgart, Germany, September 1998. Springer-Verlag.
- [PPC99] Robert Pinheiro, Alex Poylisher, and Hamish Caldwell. Mobile agents for aggregation of network management data. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 130–140, Palm Springs, California, October 1999. IEEE Computer Society Press.
- [PS97] Holger Peine and Torsten Stolpmann. The architecture of the Ara platform for mobile agents. In *Proceedings of the First International Workshop on Mobile Agents*, volume 1219 of *Lecture Notes in Computer Science*, pages 50–61, Berlin, Germany, April 1997. Springer-Verlag.
- [QV99] Pierre-Antoine Queloz and Alex Villazón. Composition of services with mobile code. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 176–189, Palm Springs, California, October 1999. IEEE Computer Society Press.
- [RASS97] M. Ranganathan, Anurag Acharya, Shamik Sharma, and Joel Saltz. Network-aware mobile programs. In *Proceedings of the 1997 USENIX Technical Conference*, pages 91–104, 1997.

- [RBM00] M. Ranganathan, Marc Bednarek, and Doug Montgomery. A reliable message delivery protocol for mobile agents. In *Proceedings of the Second International Symposium on Agent Systems and Applications and Fourth International Symposium on Mobile Agents (ASA/MA2000)*, volume 1882 of *Lecture Notes in Computer Science*, pages 206–220, Zurich, Switzerland, September 2000. Springer-Verlag.
- [RSGM99] M. Ranganathan, Virgine Schaal, Virginie Galtier, and Doug Montgomery. Mobile streams: A middleware for reconfigurable distributed scripting. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 162–175, Palm Springs, California, October 1999. IEEE Computer Society Press.
- [SBB<sup>+</sup>00a] Niranjani Suri, Jeffrey M. Bradshaw, Maggie R. Breedy, Paul T. Groh, Gregory A. Hill, Renia Jeffers, Timothy S. Mitrovitch, Brian R. Pouliot, and David S. Smith. NOMADS: toward a strong and safe mobile system. In *Proceedings of the Fourth International Conference on Autonomous Agents*, pages 163–164. ACM Press, June 2000.
- [SBB<sup>+</sup>00b] Niranjani Suri, Jeffrey M. Bradshaw, Maggie R. Breedy, Paul T. Groh, Gregory A. Hill, and Renia Jeffers. Strong mobility and fine-grained resource control in NOMADS. In *Proceedings of the Second International Symposium on Agent Systems and Applications and Fourth International Symposium on Mobile Agents (ASA/MA2000)*, volume 1882 of *Lecture Notes in Computer Science*, pages 2–15, Zurich, Switzerland, September 2000. Springer-Verlag.
- [SdD98] Alberto Silva, Miguel Mira da Silva, and José Delgado. An overview of AgentSpace: A next-generation mobile agent system. In *Proceedings of the Second International Workshop on Mobile Agents*, volume 1477 of *Lecture Notes in Computer Science*, pages 148–159, Stuttgart, Germany, September 1998. Springer-Verlag.
- [SDSL99] George Samaras, Marios D. Dikaiakos, Constantinos Spyrou, and Andreas Liverdos. Mobile agent platforms for Web databases: A qualitative and quantitative assessment. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 50–64, Palm Springs, California, October 1999. IEEE Computer Society Press.
- [SG90] James W. Stamos and David K. Gifford. Remote execution. *ACM Transactions on Programming Languages and Systems*, 12(4):537–565, October 1990.
- [SH99] Tammo Spalink and John H. Hartman. The effects of a mobile agent on file service. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 42–49, Palm Springs, California, October 1999. IEEE Computer Society Press.
- [SSY00] Takahiro Sakamoto, Taturou Sekiguchi, and Akinori Yonezawa. Bytecode transformation for portable thread migration in Java. In *Proceedings of the Second International Symposium on Agent Systems and Applications and Fourth International Symposium on Mobile Agents (ASA/MA2000)*, volume 1882 of *Lecture Notes in Computer Science*, pages 16–21, Zurich, Switzerland, September 2000. Springer-Verlag.
- [TR99] Wolfgang Theilmann and Kurt Rothermel. Disseminating mobile agents for distributed information filtering. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 152–161, Palm Springs, California, October 1999. IEEE Computer Society Press.
- [TRV<sup>+</sup>00] Eddy Truyen, Bert Robben, Bart Vanhaute, Tim Coninx, Wouter Joosen, and Pierre Verbaeten. Portable support for transparent thread migration in Java. In *Proceedings of the Second International Symposium on Agent Systems and Applications and Fourth International Symposium on Mobile Agents (ASA/MA2000)*, volume 1882 of *Lecture Notes in Computer Science*, pages 29–43, Zurich, Switzerland, September 2000. Springer-Verlag.
- [Tsc97] Christian F. Tschudin. Open resource allocation for mobile code. In *Proceedings of*

- the First International Workshop on Mobile Agents*, volume 1219 of *Lecture Notes in Computer Science*, pages 186–197, Berlin, Germany, April 1997. Springer-Verlag.
- [Tsc99] Christian F. Tschudin. Mobile agent security. In Matthias Klusch, editor, *Intelligent Information Agents*, chapter 18, pages 431–445. Springer-Verlag, 1999.
- [WBDF98] Christian Wicke, Lubomir F. Bic, Michael B. Dillencourt, and Munehiro Fukuda. Automatic state capture of self-migrating computations in MESSENGERS. In *Proceedings of the Second International Workshop on Mobile Agents*, volume 1477 of *Lecture Notes in Computer Science*, pages 68–79, Stuttgart, Germany, September 1998. Springer-Verlag.
- [WPW<sup>+</sup>97] David Wong, Noemi Paciorek, Tom Walsh, Joe DiCelie, Mike Young, and Bill Peet. *Concordia*: an infrastructure for collaborating mobile agents. In *Proceedings of the First International Workshop on Mobile Agents*, volume 1219 of *Lecture Notes in Computer Science*, pages 86–97, Berlin, Germany, April 1997. Springer-Verlag.
- [WS99] Pawel T. Wojciechowski and Peter Sewell. Nomadic Pict: Language and infrastructure design for mobile agents. In *Proceedings of the First International Symposium on Agent Systems and Applications and Third International Symposium on Mobile Agents (ASA/MA99)*, pages 2–12, Palm Springs, California, October 1999. IEEE Computer Society Press.